



CT5704+e56D ´

° \_?ô93

- Q +e0 ° 9L€ œ (   
 ¼ ë ¼ 0 ¢ 9 8

+k5< Ø#• e 6!t ð p E ž †g : p =Ũ l p Lz ,4ú F F?+^ æ ÁLü F ž , Â † •+kD% ¶ e ,  
+k"J ]730i Ð %M– > : p G>á Ø#•4ð5<´ LH "1×F%µ F7 6 `5 † • -B9 l,º Ú#w+k Á ,!š Ú#w  
+k Á ^4ð5< ž \* Ý+U 6 `Ú +k p Ç < Ũ l p Ø#• jM–F F `+k p , Ø#• j g P Ý+U U Ê+k Á , <F `  
ä g,º+k Á -5 Eý †,´ C,º t ] Ã5 EýN)NÇ@ .7 = ð# † • ¶ e :\*< , 6 D+g LCD... t/p > o ¢  
-,º L g73 Ø#• 0>á Að,º4ð5< L1×F%º,º - %º f5¢ {LÒ >



6 = Œ73(¬&ŕ

1 = Ø#• < ^ Ĩ ÷ f A,º+k5< =+k"J4ðD% = Ñ"j Ñ"J1×F%º,ºK0AðD% º

2 = Ø#• < ^ Ĩ ÷ f A,º+k5< =+k"J4ðD% c,º ãD% Â.#D% {LÒ

3 = ´ LŸ S ¬ LŸ+kD%

4 = ´>áF¢- ...,º Ý Â <4ð-

5 = ´ f µ A,º+k# Ñ ĩ4ðD% c,º ãD% Â.#D% {LÒ

6 = : p » , Ú-#w+k Á>ž Œ73 , %4ð ]#•H 12 600V ,º Ú =-#w+k Á Æ

AC 12~600V (50~60Hz) ±2.5%

DC — 12~600 V ±2.5%

7 = : p,º t/p ... % t/p vAð5¢,º : Œ)½1•4Ý = :5L.7 =8 Dá,º+k"—+kH û ë =#•H f,º LG +k

Á r = v#• LG +k Á e Ú#w L-#w LG Q ÁL +kAœ/p1\ -

8 = : p ?8 ð Œ73 , % ð#•8 Dá,º : (ï ë -FPEý LCD... t/p 0 > , Ñ µ+^6; ? ~ ø69

9 = Ũ | p,° t/p ... % t/p : p : ,° Ũ)½1•4Ý = :5L.7 = : p,°+k"—+kH ũ ë 8 Dá,°+k"—+k  
H ũ ë = Ø#• f,° Ú#w+k Á U Ê - L +kAœ/p1\ -  
10 = Ũ | p %8 Þ L • ÞB98,&« ... Ü  
11 = Ũ | p Â : pG3 - =M•N) Ũ73  
12 = Ũ | p8 Þ © p Ũ73(C»Eý 10 <JŨ ?Kd ' ©8 Þ ©L#+k\$Æ)  
13 = Ũ | p LCD... \ ?7 • Ũ73 , ð Ä ^•4ð C8¥,° Ê+^ p > c Ê+^  
14 = Ũ | p Â : pG3Gf = ? •+k1^ Ũ73 , ð ^U Í,° ũ ë A Ø#•4ð5<  
15 = % ÑLz Ũ : p+^ Ÿ { L p < P ` -  
16 =5 °3] , (~ 06F+^ , ð Ä p \

Â = ¶ e ø |

: p ¶ e | ¢

1 = EÉ 0 - Æ125 kHz

2 = LG +k ÁÄü a+k Á99 \* ÆDC 12~600 V ±2.5% ÇAC 12~600V(50~60Hz) ±2.5%

3 = t/p ... ÆLCD = \ Ũ73 t/p Â —(ì 4

4 = LG +k Á +k p Ü Æ 6 ] 400 V AC/DC

5 = Eý Á2± a ÆCAT III 300 V

6 = "— 1•4Ý Æ2

7 = +k\$Æ Æ1×9 V , IEC 6LR61

8 = Ũ6M Æ 6 E+k#w Æ4Ü mA Ç 6 ]+k#w Æ4Ü115 mA

9 = LŸ S ÆF 0.5 A 500 V , 6.3×32 mm

10 =\$\_ Ü99 \* Æ ' Æ 0°C 8) 40°C , 6 ] 80%,°-. /\$µ Ü ´M" 5 µ Ç Þ Ž Æ-20 °C 8)+60 °C ,

6 ] 80 % ,°-. /\$µ Ü ´M" 5 µ

11 =#- Q Ü Æ 6 ] 2000 m

12 = p . ´Q h ó h\$' µÆ190 mm×89 mm×42.5 mm

13 =H H Æ C a+k"— Æ ]4Ü360 g

14 = a+k"— Æ ]4Ü 420 g

Ů l p ¶ e | ¢

1 = D D`\$' Ü Æ D D`\$' Ü é Ä C^ - % Ê+^

2 = 4õ5< Ð f W E Æ < · Ê+^ Æ ]4Ü 0 8) 2 m , · Ê+^ Æ ]4Ü 0 8) 0.5 m Ç <)" 4õ %Êô 2.5 m

3 = +k5‡+k ÁAü a Æ ]4Ü0 8) 0.4 m

4 = t/p ... Æ LCD = \ Ö73 t/p Â —(i 4

5 = +k\$Æ Æ 6×1.5 V , IEC LR03

6 = Ö6M Æ 6 E+k#w Æ 4Ü mA Ç 6 ]+k#w Æ 4Ü9 mA

7 = \$ \_ Ü99 \* Æ ' Æ 0 °C 8) 40 °C , 6 ] 80%ß-. /\$µ Ü ´M" 5 µ▷ Þ Ž Æ -20 °C 8)+60 °C ,  
6 ] 80 %,°-. /\$µ Ü ´M" 5 µ▷

8 = #- Q Ü Æ 6 ] 2000 m

9 = p . ´Q h ó h\$' µ Æ 241.5 mm×78 mm×38.5 mm

10 = H H Æ C a+k"— Æ ]4Ü280 g , a+k"— Æ ]4Ü 350 g